This sample form is provided as a tool for enforcement agencies to use in the verification or certification of the mandatory requirements of the 2016 CALGreen Code. It is intended to provide a method for enforcement agencies to use to assign or specify other entities that may provide certification of compliance with various measures in the 2016 CALGreen Code.

Note: Although every effort has been made to represent the code text to meet the mandatory CALGreen requirements, enforcement agencies should assure that the features or measures exactly meet the requirements of binding verification for local purposes.

2016 CALGreen INSTALLATION CERTIFICATE RMM								
Residential Mandatory Mea	asures (F	RMM)						
Site Address:						Permit Number:		
Feature or Measure	Enforcing w		specify er verificatio	Verification				
	Enforcing Agency	Installer  All	Designer  All	Third party All	Date	Signature and title of person who verified compliance with measure		
PLANNING AND DESIGN								
Site Development								
<b>4.106.2 Storm water drainage and retention during construction.</b> A plan is developed and implemented to manage storm water drainage during construction.								
<b>4.106.3 Grading and paving.</b> The site shall be planned and developed to keep surface water away from buildings. Construction plans shall indicate how site grading or a drainage system will manage all surface water flows.								
4.106.4 Electric vehicle (EV) charging for new construction. Provide capability for electrical vehicle charging in one- and two-family dwellings and in townhouses with attached private garages; and 3 percent of total parking spaces, as specified, for multifamily dwellings.								
ENERGY EFFICIENCY		<u>'</u>						
General								
<b>4.201.1 Scope.</b> Residential buildings shall meet or exceed the minimum standard design required by the 2016 California Energy Code.	See Title 24, Part 6, for compliance forms and necessary documentation required by the 2016 California Energy Code. Applies to low-rise residential, high-rise residential, and hotels/motels.							
WATER EFFICIENCY AND CONSERV	ATION			1				
<b>4.303.1.1 Water closets.</b> The effective flush volume of all water closets shall not exceed 1.28 gallons per flush.								

## 2016 CALGreen INSTALLATION CERTIFICATE RMM2 **Residential Mandatory Measures (RMM)** Site Address: **Permit Number: Enforcing Agency to specify entity which Feature or Measure** Verification will provide verification **Enforcing** Installer Designer **Third** Signature and title of Agency party person who verified **Date** compliance with П measure ΑII ΑII ΑII ΑII WATER EFFICIENCY AND CONSERVATION (Continued) П 4.303.1.2 Urinals. The effective flush volume of wall-mounted urinals shall not exceed 0.125 gallons per flush. The effective flush volume of all other urinals shall not exceed 0.5 gallons per flush. П 4.303.1.3.1 Single Showerhead. П $\Box$ Showerheads shall have a maximum flow rate of not more than 2.0 gallons per minute at 80 psi. Showerheads shall be certified to the performance criteria of the U.S. EPA WaterSense Specification for Showerheads. Effective July 1, 2018: Showerheads shall have a maximum flow rate of 1.8 gallons per minute at 80 psi. 4.303.1.3.2 Multiple showerheads serving one shower. When a shower is served by more than one showerhead, the combined flow rate of all showerheads and/or other shower outlets controlled by a single valve shall not exceed 2.0 gallons per minute at 80 psi, or the shower shall be designed to allow only one shower outlet to be in operation at a time. Effective July 1, 2018: Combined flow rate shall not exceed 1.8 gallons per minute at 80 psi. П П П 4.303.1.4.1 Residential lavatory faucets. The maximum flow rate of residential lavatory faucets shall not exceed 1.2 gallons per minute at 60 psi. The minimum flow rate of residential lavatory faucets shall not be less than 0.8 gallons per minute at 20 psi. 4.303.1.4.2 Lavatory faucets in common and public use areas. The maximum flow rate of lavatory faucets installed in common and public use areas (outside of dwellings or sleeping units) in residential buildings shall not exceed 0.5 gallons per minute at 60 psi.

2016 CALGreen INSTALLATION CERTIFICATE RMM2							
Residential Mandatory Measures (RMM)							
Site Address:					Permit Number:		
Feature or Measure	Enforcing A will		specify ent verification	Verification			
	Enforcing Agency	Installer  All	<b>Designer</b> All	Third party	Date	Signature and title of person who verified compliance with measure	
WATER EFFICIENCY AND CONSER	VATION (Cont	inued)					
<b>4.303.1.4.3 Metering faucets</b> . Metering faucets when installed in residential buildings shall not deliver more than 0.25 gallons per cycle.							
4.303.1.4.4 Kitchen faucets. The maximum flow rate of kitchen faucets shall not exceed 1.8 gallons per minute at 60 psi. Kitchen faucets may temporarily increase the flow above the maximum rate, but not to exceed 2.2 gallons per minute at 60 psi, and must default to a maximum flow rate of 1.8 gallons per minute at 60 psi. Note: Where complying faucets are unavailable, aerators or other means may be used to achieve reduction.							
Outdoor Water Use							
<ul> <li>4.304.1 Outdoor potable water use in landscape areas. After December 1, 2015, new residential developments with an aggregate landscape area equal to or greater than 500 square feet shall comply with one of the following options:</li> <li>1. A local water efficient landscape ordinance or the current California Department of Water Resources' Model Water Efficient Landscape Ordinance (MWELO), whichever is more stringent, or</li> <li>2. Projects with aggregate landscape areas less than 2500 square feet may comply with the MWELO's Appendix D Prescriptive Compliance Option.</li> </ul>							

2016 CALGreen INSTALLATION CERTIFICATE RMM2							
Residential Mandatory Measures (RMM)							
Site Address:					Permit Numl	oer:	
Feature or Measure	Enforcing Agency to specify entity which will provide verification				Verification		
	Enforcing Agency	Installer	Designer	Third party	Date	Signature and title of person who verified	
	All	All	□ All	All	Date	compliance with measure	
MATERIAL CONSERVATION AND R	ESOURCE EF	FICIENCY	'		•		
Enhanced Durability and Reduced Maintenance							
4.406.1 Rodent proofing. Annular spaces around pipes, electric cables, conduits or other openings in sole/bottom plates at exterior walls shall be protected against the passage of rodents by closing such openings with cement mortar, concrete masonry or a similar method acceptable to the enforcing agency.							
Construction Waste Reduction, Disposal and Recycling							
4.408.1 Construction waste management. Recycle and/or salvage for reuse a minimum of 65 percent of the nonhazardous construction and demolition waste in accordance with either Section 4.408.2, 4.408.3 or 4.408.4, or meet a more stringent local construction and demolition waste management ordinance.							
Building Maintenance and Operation							
4.410.1 Operation and maintenance manual. An operation and maintenance manual in compliance with Items 1-10 shall be placed in the building.							
4.410.2 Recycling by occupants.  Where 5 or more multifamily dwelling units are constructed on a building site, provide readily accessible areas that serve the entire building and are identified for the depositing, storage and collection of non-hazardous materials for recycling, including (at a minimum) paper, corrugated cardboard, glass, plastics, organic waste, and metals or meet a lawfully enacted local recycling ordinance, if more restrictive.  Exception: Rural jurisdictions that meet and apply for the exemption in Public Resources Code Section 42649.82(a)(2)(A) et seq. will be exempt from the organic waste portion of this section.							

2016 CALGreen INSTALLATION CERTIFICATE RMM2 Residential Mandatory Measures (RMM) Site Address: Permit Number:							
Feature or Measure	Enforcing Agency to specify entity which will provide verification				Verification		
	Enforcing Agency	Installer	Designer	Third party	Date	Signature and title of person who verified	
	□ All	□ All	□ All	□ All	- 333	compliance with measure	
ENVIRONMENTAL QUALITY							
Fireplaces							
4.503.1 General. Any installed gas fireplace shall be a direct-vent sealed-combustion type. Any installed woodstove or pellet stove shall comply with US EPA New Source Performance Standards (NSPS) emission limits as applicable, and shall have a permanent label indicating they are certified to meet the emission limits. Woodstoves, pellet stoves and fireplaces shall also comply with applicable local ordinances.							
Pollutant Control							
4.504.1 Covering of duct openings and protection of mechanical equipment during construction. Duct openings and other related air distribution component openings shall be covered during construction.							
<b>4.504.2.1 Adhesives, sealants and caulks.</b> Adhesives, sealants and caulks shall be compliant with VOC and other toxic compound limits.							
<b>4.504.2.2 Paints and coatings.</b> Paints, stains and other coatings shall be compliant with VOC limits.							
<b>4.504.2.3 Aerosol paints and coatings.</b> Aerosol paints and coatings shall be compliant with productweighted MIR limits for ROC and other toxic compounds.							
<b>4.504.2.4 Verification.</b> Documentation shall be provided to verify that VOC limit- compliant finish materials have been used.							
<b>4.504.3 Carpet systems.</b> Carpet and carpet systems shall be compliant with VOC limits.							

## 2016 CALGreen INSTALLATION CERTIFICATE RMM2 **Residential Mandatory Measures (RMM)** Site Address: **Permit Number: Enforcing Agency to specify entity which Feature or Measure** Verification will provide verification **Enforcing** Installer Designer **Third** Signature and title of **Agency** party person who verified Date compliance with П measure All ΑII ΑII **ENVIRONMENTAL QUALITY (Continued)** 4.504.4 Resilient flooring systems. At П П П least 80% of floor area receiving resilient flooring shall be compliant with VOC limits. П П П 4.504.5 Composite wood products. Hardwood plywood, particleboard and medium density fiberboard (MDF) used on the interior or exterior of the building shall comply with low formaldehyde emission standards. See Section 4.504.5.1 regarding documentation. Interior Moisture Control 4.505.2 Concrete slab foundations. Concrete slab-on-grade foundations with vapor retarders shall have a capillary break installed. 4.505.3 Moisture content of building П materials. Moisture content of building materials used in wall and floor framing is checked to be 19 percent or less before enclosure. **Indoor Air Quality and Exhaust** 4.506.1 Bathroom exhaust fans. П П Bathrooms shall be mechanically ventilated and ducted to terminate outside the building and comply with Items 1 and 2. **Environmental Comfort** 4.507.2. Heating and air conditioning П П system design. Heating and air conditioning systems shall be sized, designed, and equipment is selected using the following methods: 1. Establish heat loss and heat gain values according to ANSI/ACCA 2 Manual J - 2011 or equivalent. 2. Size duct systems according to ANSI/ACCA 1 Manual D - 2014 or equivalent. 3. Select heating and cooling equipment according to ANSI/ACCA 3 Manual S - 2014 or equivalent.

2016 CALGreen INSTALLATION CERTIFICATE RMM2 Residential Mandatory Measures (RMM)								
Feature or Measure	Enforcing A		specify ent	Verification				
	Enforcing Agency 	Installer  All	<b>Designer</b> All	Third party     All	Date	Signature and title of person who verified compliance with measure		
INSTALLER AND THIRD PARTY QU	ALIFICATION	S						
Qualifications								
<b>702.1 Installer training.</b> HVAC system installers are trained and certified in the proper installation of HVAC systems.								
<b>702.2 Special inspection.</b> Special inspectors employed by the enforcing agency must be qualified and able to demonstrate competence in the discipline they are inspecting.								
Verifications								
<b>703.1 Documentation.</b> Verification of compliance with this code shall include construction documents, plans, specifications, builder or installer certification, inspection reports, or other methods acceptable to the enforcing agency which show substantial conformance.								

2016 CALGreen INS	TALLATIO	N CERTIFICA	TE	RMM2
Residential Mandatory Me	asures (RMN	1)		
Site Address:			Permit Number:	
The following section shall be comp and/or construction of the project.	leted by a person/	persons with overall resp	oonsibility for the planning,	design
	DECLARA	ATION STATEMENT		
Section 1 Design Verification				
Complete all parts of Section 1 "Desigr		ubmit completed checklist	(Columns 1 and 2) with the pla	ans and
The owner, licensed design professi reviewed the plans and understand to accordance with the requirements s	that the items che	cked above have been in	corporated into the project p	
Owner or Responsible Person's Nan	ne:	Owner or Responsible F	Person's Signature:	
Date Signed:	Position/Title:			
Licensed Design Professional Name	):	Licensed Design Profes	sional's Signature:	
Date Signed:	Position/Title:			
Qualified Individual Name:		Qualified Individual's Si	gnature:	
Date Signed:	Position/Title:			
Building Department Plan Reviewer:		Building Department Pla	an Reviewer's Signature:	
Date Signed:	Position/Title:			
Section 2 Implementation Verificatio	o <u>n</u>			
Complete, sign and submit the completed Verification" to the Building Departmen	· ·	3 3	es on Section 2 "Implementation	on
have inspected the work and have constructed in accordance with this requirements set forth in the 2016 C	<b>Residential Mand</b>	atory Measures Checklist		
Local Building Inspector/s and/or CALGreen Special Inspector/s (whe Name:	re required)	Local Building Inspecto Signature:	r/s and/or CALGreen Specia	Il Inspector/s
Date Signed:	Position/Title:			
Owner or General Contractor Name:	<u> </u>	Owner or General Contr	ractor's Signature:	
Date Signed:	Position/Title:			
				_